

## Long reach

## BROCHURE

Categorie excavator	Model	Max. digging reach (m)	Max. digging height	Max. digging depth (m)	Boom length (m)	Arm length (m)	Counter-weight	Recommended GP bucket		Recommended ditch bucket	
								Model*	Volume (m3)	Model*	Volume (m3)
16-20 ton	SLR 18 - 13.5	13.5	11.1	10.7	7.6	5.5	1.5 ton	GP 340	0.34	DC 390	0.39
20-24 ton	SLR 21 - 15.3	15.3	12.4	11.6	8.5	6.2	1.5 ton	GP 400	0.40	DC 450	0.45
24-27 ton	SLR 25 - 16.8	16.8	13.1	12.8	9.2	6.7	1.5 ton	GP 450	0.45	DC 510	0.51
	SLR 25 - 18.3	18.3	14.0	14.2	10.2	7.8	2.5 ton	GP 400	0.40	DC 450	0.45
27-32 ton	SLR 30 - 17.5	17.5	14.7	13.5	10.0	7.0	2.0 ton	GP 510	0.51	DC 580	0.58
	SLR 30 - 18.4	18.4	15.0	14.5	10.5	7.5	2.5 ton	GP 450	0.45	DC 510	0.51
32-40 ton	SLR 36 - 18.4	18.4	14.0	14.7	10.5	7.5	2.8 ton	GP 660	0.66	DC 730	0.73
	SLR 36 - 19.7	19.7	15.0	15.8	11.0	8.0	3.2 ton	GP 510	0.51	DC 580	0.58
	SLR 36 - 20.6	20.6	16.4	16.4	11.4	8.6	3.2 ton	GP 400	0.40	DC 450	0.45
40-50 ton	SLR 45 - 19.7	19.7	14.7	15.2	11.0	8.0	2.8 ton	GP 920	0.92	DC 1000	1.00
	SLR 45 - 20.6	20.6	16.4	16.4	11.4	8.6	2.8 ton	GP 660	0.66	DC 730	0.73
	SLR 45 - 22.9	22.9	18.0	18.3	12.6	10.0	3.2 ton	GP 520	0.52	DC 580	0.58
60-70 ton	SLR 65 - 18.7	18.7	16.3	12.6	11.0	6.0	3.2 ton	GP 1420	1.42	DC 1500	1.50
	SLR 65 - 20.4	20.4	16.6	14.9	11.2	8.2	3.6 ton	GP 1350	1.35	DC 1410	1.41
	SLR 65 - 21.3	21.3	18.4	15.5	12.2	8.2	3.6 ton	GP 1250	1.25	DC 1300	1.30
	SLR 65 - 24.3	24.3	20.7	17.3	14.5	8.9	3.6 ton	GP 920	0.92	DC 1000	1.00
80-90 ton	SLR 85 - 23.9	23.9	18.1	16.3	13.5	9.2	3.6 ton	GP 1440	1.44	DC 1520	1.52
	SLR 85 - 27.4	27.4	20.5	19.1	15.3	10.8	4.0 ton	GP 1250	1.25	DC 1300	1.30
	SLR 85 - 30.5	30.5	23.9	23.1	17.5	12.0	4.0 ton	GP 920	0.92	DC 1000	1.00

Production: Japan or Korea